





Summary
GST-128 GST-129 Content: Pass
01)05012345678900(17)221006

	Average
Grade (Pass=1.5)	4.0/10/660
Average Bar Gain (tolerance)	13% (+33)
X dimension	0.0209* (5)
Check Character	OK (35)
Structure	
Left Margin	
Right Margin	
Aperture	29/08/2019 15:49:01
Date & Time	
Reader Info	4C580 (v0206) Resolution=20



Verification | Scan |
539477297209128

	Average
Overall Grade	B (3.3)
Reflectance	A (4.0)
Contrast	
Modulation	
Defects	
Decodability	
Decode	

OVERALL: B (3.3)
RMin: A (4.0)
RMax: A (4.0)
Threshold: A (4.0)
Reflectance Margin: A (4.0)
Symbol Contrast: B (3.3)
Edge Contrast: A (4.0)
Modulation: A (4.0)
Defects: A (4.0)
Decodability: A (4.0)



7000 series linear barcode verifier

axicon

THE BARCODE EXPERTS

Features

Verification for outercase barcodes

ISO/IEC (ANSI) compliant verification

GS1 specifications

USB powered

Lightweight and portable

Two year warranty




Results are immediately displayed on screen, and reports can be printed or e-mailed for remote diagnosis. Reports may be saved automatically to support ISO 9001 quality control procedures. Simple user-friendly calibration, and configuration of how results are displayed. This verifier is perfect for product manufacturers, label printers, printers and packagers, and pre-press studios. It is widely used by major retailers worldwide.

Axicon 7015

Outercase barcode verifier


The Axicon 7015 barcode verifier is designed to verify large linear barcodes with a maximum width (including quiet zones) of 195mm. This means it can be used to check all barcodes used in general distribution, whether they appear on outer cases or on pallet labels (EAN-13, UPC-A, ITF-14 and GS1-128). For anyone printing 100% sized ITF-14 symbols, or A5 or larger pallet labels, this verifier is perfect.



Axicon 7025-S

High speed Outercase barcode verifier


The 'S' range of Axicon verifiers has a continuous scan feature, which means that obtaining at least ten different readings throughout the height of the barcode (as required by ISO/IEC) is much faster. Simply place the verifier slightly above or below the barcode, press the trigger and slide the verifier over the code – in less than a second you can have results of up to 100 scans of the code at different points in the bar height.



Symbologies verified



Company Name	
COMPANY ADDRESS TEL.: COMPANY PHONE NUMBER, FAX: COMPANY FAX NUMBER	
SSCC 05012345000234564	Product Description product description
Content 05012345678900	Count 110
Use by 25/12/16	Batch No. 123445
 (02)05012345678900(17)161225(10)123445	
 (00)05012345000234564(37)0110	



SSCC Pallet Label

Aperture reference

The software automatically identifies the symbology and its bar width (x-dimension) and adjusts the aperture size to comply with the symbology specifications and relevant ISO/IEC standard.

Free licence software

The verifier will analyse according to ISO/IEC 15416.

In addition the software can also check applications, such as:

GS1 General Specifications

Data content checking


Job Reference

Product Lookup

Static reflectance measurements

Analysis of bars and space dimensions

And more....




Reporting / Saving

Verification reports can be saved in various formats including:

PDF
HTML
CSV
TXT

Reports will include all ISO verification parameter grades in ISO/ANSI format.



Average Grade (Pass=1.5):	C (2.2)	
Average Bar Gain (tolerance):	12% (± 33.0%)	
Check Character:	OK (43)	
	Pass Scans	Fail Scans
Structure	1..10	
Left Margin	1..10	
Right Margin	1..10	
	Percentage Values	Average Grades
Minimum Reflectance	15%	A (4.0)
Maximum Reflectance	85%	A (4.0)
Threshold	50%	A (4.0)
Symbol Contrast	69%	A (4.0)
Min. Edge Contrast	53%	A (4.0)
Modulation	76%	A (4.0)
Defects	4%	C (2.2)
Decodability	39%	A (4.0)
Decode		

21 CFR part 11



Auto saving of reports and user permission controls features enable 21 CFR part 11 compliance.

IQ / OQ / PQ



Installation, operational and performance qualification available. Comprises documentation, results forms and performance test cards.



Software languages available

English

French (Français)

Spanish (Español)

Dutch (Nederlands)

Chinese (中文)
Simplified | Traditional

German (Deutsch)

Czech (Čeština)

Japanese (日本人)

Polish (Polski)

Italian (Italiano)

Korean (한국어)

Danish (Dansk)

Thailand (ไทย)

Hardware Specifications

Dimensions	215 x 125 x 95mm (8.4"x 4.9" x 3.7")
Weight	1.18 kg (41.6 oz)
Construction	ABS plastic, CCD sensor, LED illumination
IP options	Also available with IP50 (60529) rated protection. Field of view 190mm
Power consumption	Current draw 150mA at 5v – supplied from USB-2 host
Wavelength of light	660 nm (red)
Calibration	N.I.S.T. traceable calibration card with certificate included
Carry case	Supplied for transport and storage
Environmental	Operating temperature: 10° to 40°C - Storage temperature: -20° to 70°C Relative humidity: 25% to 80% @ 40°C non-condensing
Regulatory approvals	CE certified, RoHS compliant



Contact

Axicon Auto ID Limited

Village Farm

Church Road

Weston on the Green

Oxfordshire

OX25 3QP

UK



Tel: +44 (0)1869 351155

Email: info@axicon.com

Web: www.axicon.com

Global office locations available on our website

